



+90 276 223 30 01



info@mexxsun.com
www.mexxsun.com

mexxSUN
YENILENEBİLİR ENERJİ LTD. ŞTİ.

Specifications	MEXPV-32 DC SİGORTA
Kutup <i>Pole</i>	1P
Anma Gerilimi Ue (VDC) <i>Rated Voltage Ue (VDC)</i>	1000
Anma Akımı (A) <i>Rated Current in (A)</i>	4,6,8, 10, 12, 16,20,25,32,40,50,63

Connection And Installation	
Bağlantı (mm2) <i>Connection(mm2)</i>	2.5 -10
Çalışma Sıcaklığı(°C) <i>Working Temperature(°C)</i>	-30 - +70
Direnç ve Nemli Sıcak <i>Resistance And Damp Hot</i>	Class 2
Rakım(m) <i>Altitude(m)</i>	≤2000
Bağıl Nem <i>Relative Humidity</i>	≤95%
Koruma Sınıfı/Derecesi <i>Protection Class/Degree</i>	IP20
Kirlilik <i>Pollution</i>	3
Kurulum Ortamı <i>Installation Environment</i>	Belirgin bir şok ve titreşim yok - No obvious shock and vibration
Kurulum Sınıfı/Türü <i>Self Discharge</i>	Class 111/DIN rail

Kablolama Şeması - Wiring Diagram

